



Customer		
Customer Address	Delivery Address (if different)	Page _____ of _____
		Goods
		VAT
		Total
Contact	Delivery Method	Order Date
Tel	Despatch Route	Delivery Date
Fax	Customer Ref	
Email	Sales Contact	

**OUTSIDE VIEW ONLY**

**LIST CODE**

**OUTER FRAME**

Triple Track (210mm)

**INTERLOCKS**

Standard 94mm (006.1986)

Slim not available on triple track

**REINFORCING**

3097/1096 Out (37mm)

3099/1097 Out (60mm)

3099/1098 Out (60mm)

**39mm ADD ONS (015.0183)**

Head

Cill

Left

Right

Trickle Vents

**FIXING LUGS (056.6020)**

**THRESHOLD**

(Supplied as standard)

**DO NOT FIX THROUGH THE THRESHOLD**

**NO CILL**

**NO CILL AVAILABLE**

**CILL PRESSING**

**DO NOT FIX THROUGH THE THRESHOLD**

RP110 110 x 36

UTL036 60 x 40

UTL035 50 x 30

No Cill/Pressing Required

**GLAZING (28mm Standard)**

**Planitherm**

Total + Argon, Thermobar

**Unglazed**

**Other (Specify in Notes)**

Max Glazing uses 43mm bead. Gaskets adjusted to suit actual glazing thickness?

**EXTRUSION COLOUR**

<b>External</b>	<b>Finish</b>
<b>Internal</b>	<b>Finish</b>
White Gloss <input type="checkbox"/>	
Grey Matt (7016M) <input type="checkbox"/>	
Black Matt (9005) <input type="checkbox"/>	

**WIND LOADING** **MINIMUM 800PA**

Post Code \_\_\_\_\_ Altitude (M) \_\_\_\_\_

Distance to Sea (Km) \_\_\_\_\_

Exposed Location?

Installation Height (M) \_\_\_\_\_

PA \_\_\_\_\_ lx \_\_\_\_\_

**ITEM DETAILS**

<b>Item</b>	<b>Qty</b>	
<b>Location</b>		
<b>Width</b>		
<b>Height</b>		
		Kit Form <input checked="" type="checkbox"/>

**HANDLE TYPE**

Lever Handles

In & Out (Locking In & Out) STD

Inside Only (No External Locking)

Inside Lever/Fingerpull Out (No External Locking)

**HANDLE COLOUR**

White

Silver (Painted RAL7040)

Black

Anthracite Grey

**PREMIUM HANDLE**

Stainless Steel

\* Meeting stile = Standard 94mm Sashes  
Handles both sides, dependant on windloading (MAX ix48).  
If 030.1099 reinforcing required, then locking is internal only.

**OVERALL SIZES TO INCLUDE CILLS & ADD-ON'S**  
(TRANSOM, MULLION & MIDRAIL MEASUREMENTS ARE EXCLUDING CILLS AND ADD-ON'S)

**NOTES**

**TERMS AND CONDITIONS / EXTRA INFO**

- Interlocks to meet windloading requirements, if reinforcing is required then it will be to the outside as standard.
- Patio sashes slide on the inside as standard.
- All patios are faced drained and must meet a minimum barrier rating of 800PA.
- Patio outer frames exceeding 6000mm in width will require splitting. If not specified on the survey, we will split optimally.
- Maximum sloping pressing length is 3000mm. Anything exceeding this will be split with a butt strap.
- Maximum sash height is 2700mm, maximum sash width is 2700mm but must not exceed 300kg.
- All sizes should be referred to in millimetres.
- On dual colour orders with white inside, the inside of the patio and the inside of the cill may have a slight variance in colour.

*All orders are subject to our terms and conditions of sale which are available at: [www.a-w-s.co.uk](http://www.a-w-s.co.uk)*