



Customer		
Customer Address	Delivery Address (if different)	Page _____ of _____
		Goods
		VAT
		Total
Contact	Delivery Method	Order Date
Tel	Despatch Route	Delivery Date
Fax	Customer Ref	
Email	Sales Contact	

**OUTSIDE VIEW ONLY** **LIST CODE**

**DOOR**

Open In  Open Out

Full Swing

All orders are subject to our terms and conditions of sale which are available at [www.A-W-S.co.uk](http://www.A-W-S.co.uk)

**Customer Signature**

Overall sizes to include cills and add-ons (transom, mullion and midrail sizes are excluding cills and add-ons)

**MASTER**

Left

Right

**EXTRUSION COLOUR**

White Gloss (RAL9910G)  Single Colour RAL/BS Matt (as standard)

Grey Matt (RAL 7016)

Black Matt (RAL 9005)

All items are:  
**800 PA**

**OVERHEAD CLOSER**

Hold Open

Non-Hold Open

**ITEM DETAILS**

Item	Qty
<b>Location</b>	
<b>Frame Width</b>	
<b>Frame Height</b>	
<b>Door Width</b>	
<b>Transom Drop</b>	
<b>Midrail Height</b>	

**Mullion Split**

**HOOKLOCK**

Number of locks

None

Full - Key in & Out

    ↳ Thumb In / Key Out

Half - Key in

    ↳ Thumb In

**ELECTRIC STRIKE**

12 Volt  24 Volt

AC  DC

Fail Safe  Fail Secure

Supplied with internal thumb turn & external override & upgraded latch

**LEVER HANDLES & LATCH**  
Tokyo Handles & Nemeff Latch

Lockable

Non-Lockable (SA Only)

White

Silver Anodised

Black

**PAD HANDLE**

None

White

Silver Anodised

Black

Powder Coated

**PREMIUM HANDLES**

D Handle 300mm, SSS, In & Out

    ↳ HAB20 Rounded (order in)

    ↳ HAB21 Offset (order in)

Pole Offset, SSS, In & Out

    ↳ 600mm

    ↳ 1200mm

    ↳ 1800mm

**CILL - DOOR**

None  150mm (SH057)

**CILL - SIDE PANEL / SCREEN**

None  150mm (SH057)

**THRESHOLD**

Single SH413  Double SH410

**GLAZING**

Single 6.8mm  Double 24mm

**GLASS**

Affordable Planitherm Total +

Unglazed

**PANIC KIT**

Single / Master Leaf

Slave Leaf

Paddle Handle

Ext Access Key & Fixed Pad

3080 Entry Trim Series

**MAG LOCK Prep**

Prep required (Timber reinf. in sash as standard)

Standard 50mm head with timber

Deep reinforced header bar

    ↳ Reinforcing inside

    ↳ Reinforcing outside

**MAG LOCK BY OTHERS**

Please note: Commercial pivot doors do not have a weather rating. In exposed areas it is possible that they can be blown open, this can lead to draughts / water ingress. Consideration for additional weathering such as a canopy or porch should be made when carrying out site surveys.

© AAS OCT24 SH