## PLEASE CHECK CAREFULLY, ONCE SIGNED OFF WE ARE UNABLE TO ACCEPT AMENDMENTS AFFORDABLE ALUMINIUM SYSTEMS LTD VISOFOLD QUICK GLAZE CO-EX SURVEY

Customer								
Customer Address			Delivery Address (if different)			Pag	Page of	
						God	ods	
						VAT	-	
						Tota	al	
Contact		[	Delivery Method			Ord	ler Date	
Tel		1	Despatch Route			Del	very Date	
Fax		(	Customer Ref					
Email		5	Sales Contact	_				
OUTSIDE VI	EW ONLY				LIST CODE			
THRESHOLD	ITEM DETAILS	EXTR	USION COLOUR	##				
Standard (50mm) Low* (15mm)	Item Qty	White	Gloss (SA018E)	<u>]</u>				
Ramps (EUD03)	Width	Grey N	Matt (RAL 7016)	]   E	External		Finish	
DOOR STACKING	Height	Black I	Matt (RAL 9005)	<u> </u>	nternal		Finish	
Open In Open Out	Location				DOC Q ASS	EMBLE	)***	KIT FORM***
SASH	NOTES							
DV220 Square								
MIDRAIL/TRANSOM DV235 109mm								
DRAINAGE	OVERALL SIZES TO INCLUDE CILLS & ADD-ON'S (TRANSOM, MULLION & MIDRAIL MEASUREMENTS ARE EXCLUDING CILLS AND ADD-ON'S)							
Face None CILL	ITEM STYLE		Tro (Tro aroom, moe		a morale mexicone mento / inc		into dillo	NB 7188 ON O
None			*	$\overline{}$				***
85mm (ETC451) 150mm (ETC457)		_ -				$\leftarrow$	M	>
190mm (ETC458) 225mm (ETC479) ADD-ON - 42mm	M ** M	<b>&gt;</b>	***	$\leftarrow$		$\leftarrow$	M	***
UN3042 Head Cill	**	M	***					*
Left Right Trickle Vents	*			<u>\</u>				
ADD-ON - 20mm		$\leftarrow$ M	***			<del></del>		*
Head Cill Left	* ←	+	M 🗆	with	rnal locking not available this style. ch Doors will have Lever	With tra min 2 1280 3 1870	ffic door max 2486 3677	No traffic door min max 2 1525 2523
HANDLE COLOUR Chrome		$\rightarrow$	* ***	Fren will h	dles on both sashes ch Doors within a bifold have Lever on Master and	4 2460 5 3075 6 3640 7 4230	4889 6151 7290 8480	4 2925 4925 6 4330 7320
White Silver			└── <b>│</b> ├── <b>│</b> *	snoo	otbolt on slave	See belo	w for DOC Q	Guidelines
Black Grey		<del></del>						
PREMIUM HANDLES SS Ergonomic Lever	TERMS AND CONDITIONS							
On Rose	Once the frames have been asser	nbled, re	-works, cut-downs	and a	any alterations will not be pos	sible. Ple	ase check	the order
On Backplate	requirements carefully.  Open In doors will have an ACDV274 'D' handle above each Debar handle. Black as standard.							
Toe and heeling kits supplied as standard.	* Low Threshold has no weathering guarantee and is not recommended for external use. DV171 is used for Open In, DV271 for Open Out.  ** Standard bifold glazing is 28mm Planitherm Total +, Argon, Black Thermobar, Toughened.							
Hinges, Rollers & Top Guides in Black	*** Doors exceeding 4000 in width or 2400 in height will be supplied in kit form. # Premium Handles will consist of Stainless Steel Ergonomic Lever and SS shootbolt handles on intermediate door.							
GLAZING  **Glazed	Doc Q comes glazed (6.8mm Lami in/Tough Out) and a high security cylinder. DOC Q must be within guidelines. Sash width between 700mm & 1200mm & max Sash height 2500mm.  ## Quick Glaze not available on Coat to Order single colours.							
Unglazed Unglazed	All orders are subject to our t		3	sale	which are available at: ww	vw.a-w-:	s.co.uk	