



Customer		
Customer Address	Delivery Address (if different)	Page _____ of _____
		Goods
		VAT
		Total
Contact	Delivery Method	Order Date
Tel	Despatch Route	Delivery Date
Fax	Customer Ref	
Email	Sales Contact	

OUTSIDE VIEW ONLY **LIST CODE**

THRESHOLD

Standard (50mm)

Low* (15mm)

Ramps (EUD03)

DOOR STACKING

Open In

Open Out

SASH

DV220 Square

MIDRAIL/TRANSOM

DV235 109mm

DRAINAGE

Face None

CILL

None

85mm (ETC451)

150mm (ETC457)

190mm (ETC458)

225mm (ETC479)

ADD-ON - 42mm

UN3042 Head

Cill

Left

Right

Trickle Vents

ADD-ON - 20mm

Head

Cill

Left

Right

HANDLE COLOUR

Chrome

White

Silver

Black

Grey

PREMIUM HANDLES

SS Ergonomic Lever

On Rose

On Backplate

Toe and heeling kits supplied as standard.

Hinges, Rollers & Top Guides in Black

GLAZING

**Glazed

Unglazed

ITEM DETAILS

Item	Qty
Width	
Height	

EXTRUSION COLOUR ##

White Gloss (SA018E) <input type="checkbox"/>		
Grey Matt (RAL 7016) <input type="checkbox"/>	External	Finish
Black Matt (RAL 9005) <input type="checkbox"/>	Internal	Finish

Location ASSEMBLED*** KIT FORM***

DESIGNS

OVERALL SIZES TO INCLUDE CILLS & ADD-ON'S
(TRANSOM, MULLION & MIDRAIL MEASUREMENTS ARE EXCLUDING CILLS AND ADD-ON'S)

SIDE FRAME

Side Frame Fixed Only

Internally Glazed Option
ETC4011 (Short Leg)

ETC4031 (Transom 62mm Face)
Midrail match not available

Externally Glazed Option
ETC4111 (Ext glazed)

Transom/Mullion for ETC4111

ETC4130 (57mm)

ETC639 (109mm)

Opener - Alitherm 400

ETC4111 Outer

ETC4129 Int Glazed

ETC4120 Ext Glazed

Coupler (Vertical)

UN3015 (70 x 15mm)

ETC357 (76 x 25mm)

Load Bearing (24mm) inc Bay Jacks

UN3015 coupler will be used unless ix value required is too great.

Coupler (Horizontal Drained)

UN3000 (70 x 15mm)

Cill for full height sides

None

As Door

Cill for flag side frames

None

85mm (ETC451)

150mm (ETC457)

190mm (ETC458)

225mm (ETC479)

Min Sash Width 700mm
Max Sash Width 1200mm
Max Sash Height 2500mm

NOTES

Door toplight, and side frames must be fabricated separately

Restrictor 90°

Not supplied as standard
Required

French Door Handles

Master Left Master Right

All French Door combinations will have double lever handles

ETC357 & UN3042 - when used together the Add-on is split and the coupler runs from cill to the top of the Add-on.
UN3015 & UN3042 - when used together the coupler will run to the underside of the Add-on, with Add-on running full width.
Couplers are not structural, steel is recommended between bi-folds and toplights.

TERMS AND CONDITIONS

Once the frames have been assembled, re-works, cut-downs and any alterations will not be possible. Please check the order requirements carefully.

* Low Threshold has no weathering guarantee and is not recommended for external use. DV171 is used for Open In, DV271 for Open Out.

** Standard bifold glazing is 28mm Planitherm Total +, Argon, Black Thermobar, Toughened.

Bifold outer frames exceeding 6000mm in width will require splitting. If not specified on the survey, we will split optimally.

*** Doors exceeding 4000 in width or 2400 in height will be supplied in kit form.

Premium Handles will consist of Stainless Steel Ergonomic Lever and SS shootbolt handles on intermediate door.

Quick Glaze not available on Coat to Order single colours.

All orders are subject to our terms and conditions of sale which are available at: www.a-w-s.co.uk